

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

UFI: R1DP-R0XH-JP0H-TKMF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: SORMAT Oy
 Street: Harjutie 5
 Place: FIN-21290 Rusko
 Telephone: +358 207 940 200
 e-mail: sormat@sormat.com
 Internet: www.sormat.com
 Responsible Department: Technical information: sormat@sormat.com

1.4. Emergency telephone number:

Poison Information Center and Clinical Toxicology, Mainz Tel.: +49 (0) 6131 19240 (in English)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
 Skin corrosion/irritation: Skin Irrit. 2
 Serious eye damage/eye irritation: Eye Irrit. 2
 Respiratory or skin sensitisation: Skin Sens. 1
 Hazardous to the aquatic environment: Aquatic Chronic 2
 Hazard Statements:
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Toxic to aquatic life with long lasting effects.

2.2. Label elements


Regulation (EC) No. 1272/2008

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;
 Bisphenol-F-epichlorohydrin resin MM <= 700;
 1,6-Bis(2,3-epoxypropoxy)hexane

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 2 of 13

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P264 Wash hands thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P391 Collect spillage.

Special labelling of certain mixtures

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.
Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			25 - < 50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			10 - < 20 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			10 - < 20 %
	618-939-5		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)			1 - 10 %
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity
	Specific concentration limits and M-factors		
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	25 - < 50 %
	Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 3 of 13

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 4 of 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Use only outdoors or in a well-ventilated area.
- Wear personal protection equipment (refer to section 8).
- Avoid contact with skin, eyes and clothes.
- When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed.
- Store in a place accessible by authorized persons only.
- Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

- Do not store together with: Oxidising agent, strong
- Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			
Worker DNEL, acute		dermal	local	0,0083 mg/cm ²
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
Worker DNEL, long-term		inhalation	systemic	10,57 mg/m ³
Worker DNEL, long-term		inhalation	local	0,44 mg/m ³
Worker DNEL, long-term		dermal	systemic	6,0 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,0226 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	5,29 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,27 mg/m ³
Consumer DNEL, long-term		dermal	systemic	3,0 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,0136 mg/cm ²
Consumer DNEL, acute		inhalation	systemic	5,29 mg/m ³
Consumer DNEL, acute		dermal	systemic	1,7 mg/kg bw/day
Consumer DNEL, acute		dermal	local	0,0136 mg/cm ²
Consumer DNEL, long-term		oral	systemic	1,5 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	1,5 mg/kg bw/day

PNEC values

CAS No	Substance	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700	
Freshwater		0,003 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,0294 mg/kg
Secondary poisoning		0,0254 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l
Marine water		0,00115 mg/l
Freshwater sediment		0,283 mg/kg
Marine sediment		0,283 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 6 of 13

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)
 Breakthrough time: > 480 min
 Thickness of the glove material: 0,7 mm
 DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)	
Colour:	light beige	
Odour:	characteristic	
Odour threshold:	No data available	
pH-Value:		not determined

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 7 of 13

Auto-ignition temperature

Solid: not determined
 Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,49 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

Keep away from: Oxidizing agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane				
	oral	LD50 2190 mg/kg	Rat		OECD 401
	dermal	LD50 > 2000 mg/kg	Rat		OECD 402
	inhalation (4 h) vapour	LC50 0,035 mg/l	Rat		
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)				
	oral	LD50 20700 mg/kg	Mouse		
	dermal	LD50 2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Bisphenol-F-epichlorohydrin resin MM <= 700; 1,6-Bis(2,3-epoxypropoxy)hexane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700					
	Acute fish toxicity	LC50 mg/l	2,54	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	1,8 mg/l	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	2,55	48 h	Daphnia magna (Big water flea)	
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50	30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	47 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700				
	OECD 301B	16 %	28		
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane				
	OECD 301D	71 %	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700	3,3
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	0,822

BCF

CAS No	Chemical name	BCF	Species	Source
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	3,57		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 10 of 13

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste


List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9




Classification code: M7
 Special Provisions: 274 335 375 601
 Limited quantity: 5 kg
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: -

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Classification code: M7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 11 of 13

Special Provisions: 274 335 375 601
 Limited quantity: 5 kg
 Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: 274, 335, 966, 967, 969
 Limited quantity: 5 kg
 Excepted quantity: E1
 EmS: F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158 A179 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y956
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 956
 IATA-max. quantity - Passenger: 400 kg
 IATA-packing instructions - Cargo: 956
 IATA-max. quantity - Cargo: 400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5kg according A197 IATA-DGA

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 12 of 13

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment (SEVESO III):

Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,8,15.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
 (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
 ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 CAS: Chemical Abstracts Service
 CLP: Classification, Labeling and Packaging
 DMEL: Derived Minimal Effect level
 DNEL: Derived No Effect Level
 EC50: Effective concentration, 50%
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
 IMDG: International Maritime Dangerous Goods Code
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 NOEC: No Observed Effect Concentration
 OECD: Organisation for Economic Co-operation and Development
 PBT: persistent, bioaccumulative and toxic
 vPvB: very persistent and very bioaccumulative
 PNEC: Predicted No Effect Concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
 VOC: Volatile organic compound
 Aquatic Chronic 2: Long-term aquatic hazard, Category 2
 Aquatic Chronic 3: Long-term aquatic hazard, Category 3
 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. A

Revision date: 11.12.2020

Page 13 of 13

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2
 Skin Sens. 1: Skin sensitization, Category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

UFI: W4DP-80MW-VP00-GX6H

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: SORMAT Oy
Street: Harjutie 5
Place: FIN-21290 Rusko
Telephone: +358 207 940 200
e-mail: sormat@sormat.com
Internet: www.sormat.com
Responsible Department: Technical information: sormat@sormat.com

1.4. Emergency telephone number:

Poison Information Center and Clinical Toxicology, Mainz Tel.: +49 (0) 6131 19240 (in English)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Germ cell mutagenicity: Muta. 2

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May damage fertility.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

3-aminomethyl-3,5,5-trimethylcyclohexylamine;

Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine);

m-Phenylenebis(methylamine);

Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine;

Diethylenetriamine;

Phenol;

Bisphenol A

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 2 of 16

Signal word: Danger

Pictograms:



Hazard statements

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H341 Suspected of causing genetic defects.
- H360F May damage fertility.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P201 Obtain special instructions before use.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P310 Immediately call a POISON CENTER/doctor.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Contains Amines. May produce an allergic reaction.
Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 3 of 16

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			30 - < 40 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			
1950616-36-0	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			15 - < 25 %
	701-207-5		01-2119966906-20	
	Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H314 H318 H317 H412			
1477-55-0	m-Phenylenebis(methylamine)			15 - < 25 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412			
77138-45-5	Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine			< 10,5 %
	500-263-6		01-2120769506-44	
	Repr. 2, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H361f H314 H318 H317 H335			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol			5 - < 10 %
	202-013-9		01-2119560597-27	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319			
100-51-6	Benzyl alcohol			5 - < 10 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
111-40-0	Diethylenetriamine			< 7 %
	203-865-4	612-058-00-X	01-2119473793-27	
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H317 H335			
108-95-2	Phenol			1 - < 5 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H318 H373 H411			
71074-89-0	Bis[(dimethylamino)methyl]phenol			1 - < 5 %
	275-162-0			
	Skin Corr. 1B, Eye Dam. 1; H314 H318			
80-05-7	Bisphenol A			< 2 %
	201-245-8	604-030-00-0	01-2119457856-23	
	Repr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Chronic 2; H360F H318 H317 H335 H411			

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity
	Specific concentration limits and M-factors		
108-95-2	203-632-7	Phenol	1 - < 5 %
	Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 4 of 16

Further Information

SVHC list (Candidate List of Substances of Very High Concern for authorization): The product contains one of the listed substances: Bisphenol A

This mixture is placed on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
May damage fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 5 of 16

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 6 of 16

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
80-05-7	Bisphenol A, inhalable dust	-	2		TWA (8 h)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1950616-36-0	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			
Worker DNEL, long-term	inhalation	systemic		0,02 mg/m ³
Worker DNEL, acute	inhalation	systemic		2,0 mg/m ³
Worker DNEL, long-term	inhalation	local		0,6 mg/m ³
Worker DNEL, acute	inhalation	local		6,0 mg/m ³
Worker DNEL, acute	dermal	local		2,8 mg/person/day
Worker DNEL, long-term	dermal	local		0,28 mg/person/day
Worker DNEL, acute	dermal	systemic		mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)			
Worker DNEL, long-term	inhalation	systemic		1,2 mg/m ³
Worker DNEL, long-term	inhalation	local		0,2 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,33 mg/kg bw/day

PNEC values

CAS No	Substance	Value
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine water		0,009 mg/l
Freshwater sediment		0,43 mg/kg
Marine sediment		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,045 mg/kg
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	
Freshwater		0,084 mg/l
Marine water		0,0084 mg/l
Micro-organisms in sewage treatment plants (STP)		0,2 mg/l

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 7 of 16



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke. Avoid contact during pregnancy and while nursing.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: 0,7 mm
DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)	
Colour:	black / red	
Odour:	characteristic	
Odour threshold:	No data available	
pH-Value:		not applicable
Changes in the physical state		
Melting point:		not determined
Initial boiling point and boiling range:		not determined
Flash point:		not applicable
Flammability		
Solid:		not determined
Gas:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Auto-ignition temperature		
Solid:		not determined
Gas:		not applicable
Decomposition temperature:		not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 8 of 16

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,07 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 9 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 mg/kg 1030	Rat		
	dermal	ATE mg/kg 1100			
1477-55-0	m-Phenylenebis(methylamine)				
	oral	LD50 mg/kg 930	Rat		
	dermal	LD50 mg/kg 2000	Rabbit		
	inhalation (1 h) vapour	LC50 3,89 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol				
	oral	LD50 mg/kg 2169	Rat		
	dermal	LD50 mg/kg 1280	Rat		
100-51-6	Benzyl alcohol				
	oral	LD50 mg/kg 1230	Rat		
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
111-40-0	Diethylenetriamine				
	oral	LD50 mg/kg 1080	Rat		
	dermal	LD50 mg/kg 1054	Rabbit		
	inhalation vapour	ATE 0,5 mg/l			
	inhalation aerosol	ATE 0,05 mg/l			
108-95-2	Phenol				
	oral	LD50 mg/kg 650	Rat		OECD 401
	dermal	LD50 mg/kg 630	Rabbit		
	inhalation vapour	ATE 3 mg/l			
	inhalation aerosol	LC50 0,9 mg/l	8 h Rat		
80-05-7	Bisphenol A				
	oral	LD50 mg/kg 3250	Rat		
	dermal	LD50 mg/kg 3000	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 10 of 16

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine); m-Phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine; Diethylenetriamine; Bisphenol A)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol)
May damage fertility. (Bisphenol A)
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

This mixture is placed on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 11 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1477-55-0	m-Phenylenebis(methylamine)					
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)	OECD 203
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50 mg/l	15,2	48 h	Daphnia magna (Big water flea)	OECD 202
	Crustacea toxicity	NOEC	4,7 mg/l	21 d	Daphnia magna (Big water flea)	OECD 211
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol					
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)	
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus	OECD 201
	Algae toxicity	NOEC	6,25 mg/l	3 d		
111-40-0	Diethylenetriamine					
	Acute fish toxicity	LC50	430 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna	
108-95-2	Phenol					
	Acute fish toxicity	LC50	8,9 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	61,1	96 h		
	Acute crustacea toxicity	EC50	3,1 mg/l	48 h	Daphnia magna (Big water flea)	
	Crustacea toxicity	NOEC	0,16 mg/l	16 d	Daphnia magna (Big water flea)	
80-05-7	Bisphenol A					
	Acute fish toxicity	LC50	4,6 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	2,73	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	10,2	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-05-7	Bisphenol A			
	OECD 301F	74,7 - 81,4	28	

12.3. Bioaccumulative potential

The product has not been tested.

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 12 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
100-51-6	Benzyl alcohol	1,05
111-40-0	Diethylenetriamine	-5,58
108-95-2	Phenol	1,5
80-05-7	Bisphenol A	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		
108-95-2	Phenol	17,5		
80-05-7	Bisphenol A	73		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006


ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 13 of 16

Land transport (ADR/RID)


14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 Transport category: 3
 Hazard No: 80
 Tunnel restriction code: E

Inland waterways transport (ADN)


14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 14 of 16

Hazard label:

8



Special Provisions:

A3 A803

Limited quantity Passenger:

5 kg

Passenger LQ:

Y844

Excepted quantity:

E2

IATA-packing instructions - Passenger:

859

IATA-max. quantity - Passenger:

15 kg

IATA-packing instructions - Cargo:

863

IATA-max. quantity - Cargo:

50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Bisphenol A

Restrictions on use (REACH, annex XVII):

Entry 3: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 2,4,6-Tris(dimethylaminomethyl)phenol; Benzyl alcohol; Diethylenetriamine

Entry 66: Bisphenol A

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 28,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 15.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 15 of 16

Abbreviations and acronyms

- ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
- ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- CAS: Chemical Abstracts Service
- CLP: Classification, Labeling and Packaging
- DMEL: Derived Minimal Effect level
- DNEL: Derived No Effect Level
- EC50: Effective concentration, 50%
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
- IMDG: International Maritime Dangerous Goods Code
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%
- NOEC: No Observed Effect Concentration
- OECD: Organisation for Economic Co-operation and Development
- PBT: persistent, bioaccumulative and toxic
- vPvB: very persistent and very bioaccumulative
- PNEC: Predicted No Effect Concentration
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
- VOC: Volatile organic compound
- Acute Tox. 2: Acute toxicity, Category 2
- Acute Tox. 3: Acute toxicity, Category 3
- Acute Tox. 4: Acute toxicity, Category 4
- Aquatic Chronic 3: Long-term aquatic hazard, Category 3
- Eye Dam. 1: Serious eye damage/eye irritation, Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
- Repr. 1B: Reproductive toxicity, Category 1B
- Skin Sens. 1: Skin sensitization, Category 1
- Skin Sens. 1B: Skin sensitization, Category 1B
- STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2
- STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ITH-EPOXe pure epoxy (ITH 585 EPOXe (9640072946)), Comp. B

Revision date: 11.12.2020

Page 16 of 16

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)